




•HCX-7SB Series

7.0X5.0X1.20 mm



FEATURES


- Prepared frequencies can meet most of bluetooth chipsets
- Excellent heat resistance and shock resistance.
- Products that are lead-free. These can meet the requirement of re-flow profiling using lead-free solder

Electrical Specifications

Item	Type	HCX-7SB				
		6 to 7.999MHz	8 to 15.999MHz	16 to 39.999MHz	40 to 83.999MHz	84 to 100.000MHz
Frequency Range	F0	6 to 7.999MHz	8 to 15.999MHz	16 to 39.999MHz	40 to 83.999MHz	84 to 100.000MHz
Mode of Vibration		Fundamental			3 rd Overtone	
Load Capacitance	CL	10pF to Series				
Frequency Tolerance	$\Delta F / F_0$	$\pm 10\text{ppm}, \pm 30\text{ppm}, \pm 50\text{ppm}$ (At 25°C)				
Equivalent Series Resistance	ESR	100 Ω max.	60 Ω max.	40 Ω max.	70 Ω max.	60 Ω max.
Temperature Stability	TC	$\pm 10\text{ppm}, \pm 30\text{ppm}, \pm 50\text{ppm}$ (Refer to 25°C)				
Operating Temperature Range	T _{OPR}	-20~+70°C, -30~+85°C Option				
Storage Temperature Range	T _{STG}	-55~+125°C				
Shunt Capacitance	C ₀	7pF max.				
Insulator Resistance	IR	500M Ω min. (At 100V _{DC})				
Drive Level	DL	100 μ W (500 μ W max.)				
Aging	F _a	$\pm 2\text{ppm}$ max. (At 25°C, First year)				
Packing Unit		1000pcs/reel				

**Please contact us for inquiries regarding other Specifications

Mechanical Dimensions(mm)



TAIWAN:

HOSONIC ELECTRONIC CO., LTD.
 23-1 LANE 84. CHUN YING ST. SHULIN CHEN.
 TAIPEI 23804. TAIWAN
 WEB SITE: <http://www.hosonic.com>



886-2-86875200



886-2-26816456



hosonic.sales@hosonic.com

CHINA:

HANGZHOU HOSONIC ELECTRONIC CO., LTD.
 NO.242 LIANGBO ROAD. LIANGZHU TOWN.
 YUHANG DISTRICT, HANGZHOU, ZHEJIANG, CHINA
 WEB SITE: <http://www.hosonic.com>



86-571-88778189



86-571-88778857



hosonic.sales@hosonic.com

Specifications are subject to change without notice